

CARGOS		9600	9500	9400	8500	8400	8300	760	750	740
Load volume	m ³ in accordance with DIN	47.5–50 ¹	41.5–44 ¹	35.5–38 ¹	41.5	35.5	30	48.5–51 ¹	42.5–44.5 ¹	36.5–38.5 ¹
Load volume with medium compression	m ³ in accordance with DIN	95–100 ¹	83–88 ¹	71–76 ¹	82	71	60	–	–	–

Pick-up										
Clearing width	mm	2000	2000	2000	2000	2000	2000	–	–	–
Diameter	mm	320	320	320	320	320	320	–	–	–
Guide wheel tyres		16 x 6.50-8	16 x 6.50-8	16 x 6.50-8	16 x 6.50-8	16 x 6.50-8	16 x 6.50-8	–	–	–
Tine spacing	mm	61	61	61	61	61	61	–	–	–
Ground clearance with articulating drawbar raised	mm	790	790	790	790	790	790	–	–	–
Hydraulic pick-up suspension, infinitely variable		o	o	o	o	o	o	–	–	–
Central additional guide wheel pick-up (guide roller)		o	o	o	o	o	o	–	–	–

Rotor										
Rotor stub	mm	120	120	120	120	120	120	–	–	–
Main drive protection	Nm	2000	2000	2000	1800	1800	1800	–	–	–
Width	mm	1580	1580	1580	1580	1580	1580	–	–	–
Diameter	mm	860	860	860	860	860	860	–	–	–
No. of tine rows	Qty	9	9	9	9	9	9	–	–	–

Chopper unit										
Twin knives (on one level)	Qty	40	40	40	40	40	40	–	–	–
Shortest theoretical chop length	mm	38	38	38	38	38	38	–	–	–
Individual protection against foreign objects		●	●	●	●	●	●	–	–	–

Scraper floor										
Scraper floor chains	Qty	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2
Two-speed scraper floor drive		● ²	● ²	● ²	o	o	o	o ²	o ²	o ²

Chassis										
Tandem axle, 18 t, axle spacing 1525 mm ³	mm	–	–	–	–	1525	1525	–	–	1525
Tandem axle, 20 t, axle spacing 1810 mm ³	mm	–	1810	1810	1810	1810	–	–	1810	1810
Tridem axle, 27 t, axle spacing 1525 mm ³	mm	1525	1525	–	1525	–	–	1525	1525	–
Tridem axle, 30 t, axle spacing 1810 mm ³	mm	1810	1810	–	–	–	–	1810	–	–

Steering										
Steered trailing tandem axle		–	●	●	●	●	●	–	●	●
Steered trailing tridem axle		●	●	–	●	–	–	●	●	–
Electrohydraulic positive steering, tandem		–	o	o	o	o	o	–	– ⁹	– ⁹
Electrohydraulic positive steering, tridem		●	o	–	o	–	–	o ⁹	o ⁹	–

Permissible gross weight										
Tandem axle, 18 t	t	–	–	–	–	21 / 22 ⁴	21 / 22 ⁴	–	–	21 / 22 ⁴
Tandem axle, 20 t	t	–	23 / 24 ⁴	23 / 24 ⁴	23 / 24 ⁴	23 / 24 ⁴	–	–	23 / 24 ⁴	23 / 24 ⁴
Tridem axle, 27 t	t	31 ⁴	31 ⁴	–	31 ⁴	–	–	31 ⁴	31 ⁴	–
Tridem axle, 30 t	t	34 ⁴	34 ⁴	–	–	–	–	34 ⁴	–	–

Dimensions										
Overall length	mm	11940	10800	9660	10875	9735	8595	11230	10090	8950
Overall height ⁵	mm	3870–3990	3870–3990	3870–3990	3650–3990	3650–3990	3650–3870	3650–3990	3650–3990	3650–3990
Loading area	mm	9100 x 2360	7960 x 2360	6820 x 2360	7240 x 2360	6100 x 2360	4960 x 2360	8740 x 2360	7600 x 2360	6490 x 2360
Track width	mm	2100	2100	2100	2100	2100	2100	2100	2100	2100

CARGOS		9600	9500	9400	8500	8400	8300	760	750	740
Tyres⁶										
Alliance 885 Flotation Radial	600/50-22.5	–	–	–	o	o	o	o	o	o
Vredestein Flotation Pro	710/40 R 22.5	–	–	–	o	o	o	o	o	o
Vredestein Flotation Pro	620/55 R 26.5	o	o	o	o	o	o	o	o	o
Vredestein Flotation Pro	710/50 R 26.5	o	o	o	o	o	o	o	o	o
BKT Ridemax FL693M	710/50 R 26.5	o	o	o	o	o	o	o	o	o
Alliance I-380	750/45 R 26.5	o	o	o	o	o	o	o	o	o
Vredestein Flotation Pro	800/45 R 26.5	o	o	o	o	o	o	o	o	o
BKT Ridemax FL693M	710/50 R 30.5	o	o	o	o	o	o	o	o	o
Vredestein Flotation Trac	750/50 R 30.5	o	o	o	o	o	–	o	o	o

Operation										
ISOBUS-compatible		●	●	●	●	●	●	o ⁹	o ⁹	o ⁹
ISOBUS connection cable		o	o	o	o	o	o	o ⁹	o ⁹	o ⁹
EASY on board		o	o	o	o	o	o	o ⁹	o ⁹	o ⁹
OPERATOR		o	o	o	o	o	o	o ⁹	o ⁹	o ⁹
COMMUNICATOR II		o	o	o	o	o	o	o ⁹	o ⁹	o ⁹

Hydraulics										
Spool valves								LS (or 1 x sa + open return line) ⁷		3 da + 1 sa
Power-Beyond connection		o	o	o	o	o	o	o	o	o ⁹ o ⁹ o ⁹
ISO 16028 hydraulic couplings to connect to flat face		o	o	o	o	o	o	o	o	o ⁹ o ⁹ o ⁹

Additional options										
Automatic articulating drawbar control		o	o	o	o	o	o	o	–	–
Metering rollers (+ drive system) ⁸		o	o	o	o	o	o	o	o	o
Insert panels for removed metering rollers		o	o	o	o	o	o	o	o	o
Hydraulically folding filling flap with automated loading function		o	o	o	o	o	o	o	–	–
Automatic loading function via torque on the drive		o	o	o	o	o	o	o	–	–
Ultrasonic fill-level sensor		o	o	o	o	o	o	o	–	–
LED work lights package		o	o	o	o	o	o	o	o ¹⁰	o ¹⁰ o ¹⁰
LED side marker lights		o	o	o	o	o	o	o	o	o
Storage frame for loading/cutting assembly after removal		o	o	o	o	o	o	o	–	–
Channel cover for use in chopper transport		o	o	o	o	o	o	o	–	–
CLAAS PROFI CAM 3		o	o	o	o	o	o	o	–	–
Weight indicator (with hydraulic chassis only)		o	o	o	o	o	o	o	o ⁹	o ⁹ o ⁹
External display for weight indicator		o	o	o	o	o	o	o	o ⁹	o ⁹ o ⁹ o ⁹
Lift axle for tridem axle (with hydraulic chassis only)		o	o	o	o	o	o	o	o ⁹	o ⁹ –
Trailer safety snap cable for hydraulic brake		o	o	o	o	o	o	o	o	o
Hydraulic drawbar suspension		●	●	●	●	●	●	o	o	o
Underride guard at rear		–	–	–	–	–	–	o	o	o
Loading bay cover		–	–	–	–	–	–	o	o	o

¹ With platform gate extensions

² Drive on both sides

³ Mechanical suspension or with hydraulic compensation, with hydraulic suspension as an option

⁴ Permissible towbar load 3.0 t in series, optional 4.0 t, tridem always 4.0 t

⁵ Depending on tyres 30.5" / 26.5" / 22.5" and equipment with/without platform gate extensions

⁶ 10-hole rims in the standard version, tyres partly dependent on the axle

⁷ + 1 sa with hydraulically sprung chassis

⁸ Three metering rollers in the CARGOS 9000 and 8000, and two in the CARGOS 700

⁹ Deluxe model with load-sensing comfort hydraulics and full ISOBUS capability

¹⁰ Lighting management system is included in deluxe model

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.