



4 IN 1 BUCKET

Australian Designed and manufactured using only the highest quality components and materials. The Digga 4 in 1 Bucket has an extensive range to suit most machines.

Features:

- Grabbing teeth profiled on both front/rear overlap for greater grip of logs or other debris.
- Side curved sections create greater opening bucket width of 860mm.
- 1 piece heavy duty fully welded 6mm grill/hungry board with unique high visibility design, for clear vision of both front and back bucket edge.
- Standard Heavy Duty 20mm Floors.
- Optional reversible bolt on cutting edges for all 3 edges of the bucket
- Optional chisel or tiger teeth with pin on design.
- Full range available from 880mm to 2130mm.
- 12mm and 16mm floors available on request.



Ideal Use:

Grading, scraping, grapping, dozing dirt or material spreading most construction work.

Machine Suitability:

Full range available for most machine types.

STANDARD		880	900	1070	1100	1130	1225	1300	1450	1550	1600	1650	1680	1727	1800	
	Depth (Bucket Closed)	826	826	826	826	826	826	826	826	826	826	826	826	826	826	826
	Bucket Cutting Width	880	900	1070	1100	1130	1225	1300	1450	1550	1600	1650	1680	1727	1800	
	Height	643	643	643	643	643	643	643	643	643	643	643	643	643	643	
	Weight (kgs)	147	150	162	166	172	186	195	330	345	352	360	370	380	403	
	ISO Struck Volume m ³	0.09	0.09	0.11	0.11	0.12	0.13	0.14	0.20	0.22	0.22	0.23	0.23	0.24	0.25	
	ISO Heaped Volume m ³	0.11	0.11	0.14	0.14	0.15	0.16	0.17	0.26	0.28	0.29	0.30	0.31	0.32	0.33	

HIGH VOLUME		1727HV	1800HV	1880HV	2000HV	2040HV	2130HV
	Depth (Bucket Closed)	901	901	901	901	901	901
	Bucket Cutting Width	1727	1800	1880	2000	2040	2130
	Height	727	727	727	727	727	727
	Weight (kgs)	387	410	425	432	437	450
	ISO Struck Volume m ³	0.27	0.28	0.29	0.31	0.32	0.33
	ISO Heaped Volume m ³	0.36	0.37	0.39	0.42	0.43	0.45

ALSO AVAILABLE



Tilting 4 in 1 Bucket



Mini 4 in 1 Bucket